



- 1 Mounting hole
- 1 Mounting Panel ≤ 8 mm
- Dimension „a“ = 26 for Cable- $\varnothing \leq 13$
- Dimension „a“ = 29,5 for Cable- $\varnothing \geq 14$

with Strain Relief Sleeve

Crimp Connection

with additional clamping of the cable sheath

Accessories (extra order): Protective Cap for contact protection Part-No. 2-1779-7463

Cables and cable assemblies available on customer request.

Other variations: see page „Design Options“

Cable- \varnothing	Cable-Group*	Reference Cable	Part Number	Assembly Instruction
5	I	0.55L/2.3 <i>Leoni/Perivox</i>	1-4785-4702	114
8	A	1.0s/4.5s <i>Draka; 7783A Belden</i>	1-3988-4702	102
9	B	8/1 DMC 1.0Ls/4.5s <i>Draka</i>	1-3987-4702	
11	D	1.4s/6.5s <i>Draka; 7784AF Belden</i>	1-3990-4702	
12	E	11/1 PUR 1.4/6.5s <i>Draka</i>	1-3989-4702	
	N	1.75s/7.5s <i>Draka</i>	1-8495-4702	
14	F	2.2Ls/9.7s <i>Draka; 7785A Belden</i>	1-3991-4702	

*see Cable Table Triaxial Cable

The specified data serve only to describe the product and should not be considered legally binding, guaranteed properties. We reserve the right to make constructional changes, determine delivery and are not responsible for any errors and omissions.