



- 1 Guide bush:  
Impress using mandrel after the assembly has been completed correctly.
- 2 Mounting hole  
Mounting panel  $\leq 3.5$  mm  
Dimension ,a' = 26.0 for cable- $\varnothing \leq 13$   
Dimension ,a' = 29.5 for cable- $\varnothing \geq 14$

## Crimp connection or soldered connection

Accessories (extra order): Protective Cap for contact protection Part-No. 2-1780-7463

Cables and cable assemblies available on customer request.

Cable nominal- $\varnothing$	Cable Group*	Reference Cable*	Part Number	Assembly Instruction
5	I	0.55L/2.3 <i>Leoni/Perivox</i>	1-4817-4744	116
8	A	1.0s/4.5s <i>Draka</i> ; 7783A <i>Belden</i>	1-2587-4744	105
9	B	8/1 DMC 1.0Ls/4.5s <i>Draka</i>		
11	D	1.4s/6.5s <i>Draka</i> ; 7784AF <i>Belden</i>	1-2550-4744	
12	E	11/1 PUR 1.4/6.5s <i>Draka</i>	1-8500-4744	
	N	1.75s/7.5s <i>Draka</i>		
14	F	2.2Ls/9.7s <i>Draka</i> ; 7785A <i>Belden</i>	1-2551-4744	

\*see Cable Table Triaxial Cable