


a = 14.5 mm for Cable-Ø 3 up to 9 mm
 a = 16.5 mm for Cable-Ø 11 mm



Inner Conductor - Solder connection
Outer Conductor - Clamp connection



Additional clamping
 of the cable sheath
 on request

¹ Total length with
 clamping of the cable sheath

Other variations: See page „Design Options“

Cable-Ø	Cable Group*	Reference Cable 50 Ohm*	Part Number	Assembly Instruction
2	46	RG-178B; RG-196A	1-4086-2200	25
3	1	RG-174; RG-188A; RG-316	1-1000-2200	12
	2	RG-178A		
4	3	RG-122	1-1001-2200	1
	4	0.4/2.5/4.0**		
5	5	RG-55; RG-58; RG-141; RG-142; RG-303; Aircell 5; HF 195 PVC Siva	1-1002-2200	1
	64	RG-223	1-1397-2200	
	19	0.6/3.0/5.0**		
6	42	0.6/3.0/4.3**	1-1456-2200	2
	23	0.6/3.7/6.0**		
7	50	0.8/3.7/6.0**	1-1398-2200	1
	22	RG-304	1-1399-2200	
8	11	0.8/4.8/7.0**	1-1004-2200	1
	51	1.0/4.8/7.0**		
9	12	0.8/4.8/8.0**	1-1005-2200	2
11	13	1.0/6.6/9.0**	1-2150-2200	
	27	RG-8A; RG-9B; RG-115A; RG-165; RG-213; RG-214; RG-225		
11	52	1.4/6.4/9.0**	1-1400-2200	2
	28	1.2/7.2/10.5**	1-2151-2200	
11	29	0.8/7.2/10.5**	1-2152-2200	2

* see *Cable Table Coaxial Cable*

** Cable dimensions (Inner conductor/Dielectric/Cable sheath); Other dimensions: see *Cable Group-Finder*

The specified data serve only to describe the product and should not be considered legally binding, guaranteed properties. We reserve the right to make constructional changes, determine delivery and are not responsible for any errors and omissions.