



This ultra-thin and highly flexible patch cable is ideal for GIMBALS. Damar & Hagen offers cable connectors from the BNCslim series with adapted rotary sleeves for this thin coaxial cable.

BNCslim cable plugs are operated on the rotary sleeve and therefore particularly easy to connect in tight spaces.

BNCslim-Cable Plug 1-8896-1900

- Duration (mating cycles): ≥ 2000

Coaxial Cable 13-1197-1000

- Bending cycles: ≤ 1 Million

Transmission Lengths

Standard	Bit rate	max. attenuation	Application	max. length
SMPTE 292	1.5 Gb/s	20 dB	HD-SDI 1.5	22 m
SMPTE 424	3 Gb/s	20 dB	HD-SDI 3G	15 m
SMPTE 425	3 Gb/s	40 dB	UHDTV	30 m

BNCslim made by Damar & Hagen is intermateable with all common BNC-Series.

Other variations: see page „Design Options“

Description	Cut length in m	Part Number
Coaxial Cable Belden 7500A (Ø 2.8 mm) 75 Ohm, blue 13-1197-1000 with BNCslim-Cable Plug incl. blue Rotary Sleeves 1-8896-1900	0.2	21-3839-1147
	0.3	21-3840-1147
	0.4	21-3841-1147
	0.5	21-3842-1147
	0.6	21-3843-1147
	0.7	21-3844-1147
	0.8	21-3845-1147
	0.9	21-3846-1147
	1.0	21-3847-1147

The specified data serve only to describe the product and should not be considered legally binding, guaranteed properties. We reserve the right to make constructional changes, determine delivery and are not responsible for any errors and omissions.