



This thin and highly flexible patch cable is ideal for GIMBALS. Damar & Hagen offers cable connectors from the BNCslim series with adapted rotary sleeves for this thin coaxial cable. BNCslim cable plugs are operated on the rotary sleeve and therefore particularly easy to connect in tight spaces.

BNCslim-Cable Plug 1-9005-1900

- Duration (mating cycles):  $\geq 2000$

BNCslim made by Damar & Hagen is intermateable with all common BNC-Series.

Coaxial Cable 13-1201-1000

- Bending cycles:  $\leq 1$  Million

### Transmission Lengths

Standard	Bit rate	max. attenuation	Application	Video format	FPS	max. length
SMPTE 292	1.5 Gb/s	20 dB	HD-SDI 1.5	720p, 1080i (HDTV)	25p / 30p	33 m
SMPTE 424	3 Gb/s	20 dB	HD-SDI 3G	1080p	50p / 60p	22 m
SMPTE 425	3 Gb/s	40 dB	UHDTV	1080p	50p / 60p	44 m
SMPTE 2081-1	6 Gb/s	40 dB	UHDTV	4K	25p / 30p	17 m
SMPTE 2081-2	12 Gb/s	40 dB	UHDTV	4K	25p / 60p	13 m

Description	Cut length in m	Part Number
Coaxial Cable Belden 7501A (Ø 3,7 mm) 75 Ohm, blue 13-1201-1000  with BNCslim-Cable Plug 1-9005-1900 incl. blue Rotary Sleeves 2-6390-3371	0,3	21-4015-1147
	0,6	21-4016-1147
	1,0	21-4017-1147
	1,5	21-4018-1147
	2,0	21-4019-1147
	3,0	21-4020-1147
	5,0	21-4021-1147
	7,5	21-4022-1147
	10,0	21-4023-1147

Other variations: see page „Design Options“

The specified data serve only to describe the product and should not be considered legally binding, guaranteed properties. We reserve the right to make constructional changes, determine delivery and are not responsible for any errors and omissions.