

**Panel housing:**

19", 2 U, colourless anodized, 3 mm, Pitch 13.5 mm/Plug distance vertical 20 mm  
Sach-Nr. 22-1263-1011

**Front:**

2 x 32pcs., Bulkhead Insulated-Adaptor 1-8986-1953 (BNCslim)  
All Bulkhead Adaptors mounted isolated from the Panel housing.

Configuration as follows:

A01 to A32 with Bulkhead Insulated-Adaptor 1-8986-1953 (Insulating Flange: black)

B01 to B32 with Bulkhead Insulated-Adaptor 1-8986-1953 (Insulating Flange: black)

Top Row =A; Counting from left to right – each row beginning with 01.

Bulkhead Adaptors with other-coloured Insulation Flanges are possible without extra costs.

Front side with two labels above and below

**Notice:**

The configuration of all 32 Bulkhead Adaptors requires BNC cable plugs with a pitch  $\leq 13.5$  mm.  
Therefore, we recommend connectors / connecting cables from our BNCslim series (pitch 13.5 mm).

BNCslim made by Damar & Hagen is intermateable with all common BNC-Series.

Accessories (extra order): BNCslim Patch Cable

**Front view**

Illustration only similar, because Bulkhead Adaptors without Insulating Flange

**Rear view**

Illustration only similar, because Bulkhead Adaptors without Insulating Flange

**Part Number**

22-1265-1021

The specified data serve only to describe the product and should not be considered legally binding, guaranteed properties.  
We reserve the right to make constructional changes, determine delivery and are not responsible for any errors and omissions.